

AQUA FLOC

OTHER NAMES: Liquid Floc, Aluminium Sulphate solution.

DESCRIPTION

Clear, colourless liquid, slightly viscous in consistency.

USES

To combine fine particles in pool water that are too small to filter so that as larger particles, they can be vacuumed to waste or taken out by the filter.

DIRECTIONS FOR USE

1. Add to your pool a dilution rate of 100mls Aqua Floc L for every 9000L of pool water. Premix the Floc in a bucket of pool water and distribute around the perimeter of the pool.
2. Turn the pool pump onto filter for 12 hours and backwash the filter at regular intervals or as necessary.
3. Turn your pump off for 24 hours. This will allow the fine particles to settle on the floor. For best results do not swim in the pool during this time to avoid disturbing the sediment.
4. Vacuum the sediment to your drainage system and top up pool water as required. For best results repeat the following day.

STORAGE

This must be stored in its original container and must also ensure the containers are securely sealed. This product must be stored in a cool, dark, dry and well ventilated area.

PACK SIZES

20 Lt

Refer to Material Safety Data Sheet for handling and first aid instructions.



ANDREW

3 Porana Road, PO Box 33-445, Takapuna, Auckland, New Zealand
T: (649) 444 3733 F: (649) 444 3838 E: info@andrew.co.nz W: www.andrew.co.nz